

// 174BB



Air ducting - High temperature +100 °C (+212 °F)

UL 94 V0








Construction: textile fabric coated with flame resistant PVC.

Reinforcement: steel helix wire.

Application: hot air, gas, fumes extraction.

Air conditioning-ventilation.

Constant operation: -20 °C +100 °C (-4 °F +212 °F)

												
mm	in	mm	in	bar	psi	bar	psi	mm	in	%	kg/m	lb/ft
40,0	1 9/16"							20,0	0,79		0,110	0,08
51,0	2"							25,0	0,98		0,135	0,10
63,0	2 1/2"							30,0	1,18		0,170	0,12
70,0	2 3/4"							35,0	1,38		0,185	0,13
76,0	3"							40,0	1,57		0,200	0,14
80,0	3 1/8"							40,0	1,57		0,210	0,15
90,0	3 1/2"							45,0	1,77		0,240	0,17
102,0	4"							50,0	1,97		0,280	0,19
120,0	4 3/4"							60,0	2,36		0,325	0,22
127,0	5"							63,0	2,48		0,345	0,24
140,0	5 1/2"							70,0	2,76		0,380	0,26
152,0	6"							75,0	2,95		0,410	0,28
160,0	6 5/16"							80,0	3,15		0,425	0,29
180,0	7 1/16"							90,0	3,54		0,475	0,32
203,0	8"							100,0	3,94		0,535	0,36
254,0	10"							125,0	4,92		0,845	0,57
305,0	12"							150,0	5,91		1,010	0,68