

## // 2660A



### Air seeder - PVC

**Construction:** transparent PVC - abrasion and ozone resistant.

**Reinforcement:** black shock resistant rigid PVC.

**Application:** agricultural seed transfer in "Air-Flo" seeding equipments.

**Constant operation:** -5 °C +60 °C (+23 °F +140 °F)

↻		↻		↻		↻		↻		↻		↻	
mm	in	mm	in	bar	psi	bar	psi	mm	in	%	kg/m	lb/ft	
25,0	1"			8	120	24	350	113,0	4,45	70	0,295	0,20	
32,0	1 1/4"			7	100	21	300	144,0	5,67	70	0,395	0,27	
38,0	1 1/2"			6	90	18	270	171,0	6,73	70	0,515	0,35	
45,0	1 3/4"			6	90	18	270	203,0	7,99	70	0,675	0,46	
51,0	2"			5	75	15	225	230,0	9,06	70	0,765	0,52	
63,0	2 1/2"			5	75	15	225	284,0	11,18	70	1,190	0,80	
76,0	3"			5	75	15	225	342,0	13,46	70	1,520	1,03	

## // 395BT



### Hot water wash down 40 bar (600 psi) EU 10/2011 A+B+C

**Tube:** grey non-toxic PVC.

**Reinforcement:** high tensile textile cords.

**Cover:** light blue synthetic elastomer - abrasion, ozone, animal fats and vegetable oils resistant.

**Application:** hot water wash down.

Specially designed for the food and dairy industry.

Designed for 40 bar at 70° C continuous use.

240 bar minimum burst pressure at 20 °C.

Food grade.

**Constant operation:** -10 °C +70 °C (+14 °F +158 °F)

↻		↻		↻		↻		↻		↻		↻	
mm	in	mm	in	bar	psi	bar	psi	mm	in	%	kg/m	lb/ft	
12,0	15/32"	22,00	0,87	40	600	120	1750	84,0	3,31		0,340	0,23	

## // 4660L



### General purpose S&D - PVC - Standard duty FDA - EU 10/2011 A+B+C - AS 2070

**Construction:** transparent PVC - abrasion and ozone resistant.

**Reinforcement:** white shock resistant rigid PVC.

**Application:** general purpose liquid food and alcoholic beverages suction and delivery.

Sterilize with 5% soda solution.

**Constant operation:** -5 °C +60 °C (+23 °F +140 °F)

↻		↻		↻		↻		↻		↻		↻	
mm	in	mm	in	bar	psi	bar	psi	mm	in	%	kg/m	lb/ft	
20,0	13/16"			8	120	24	350	90,0	3,54	70	0,230	0,16	
25,0	1"			8	120	24	350	113,0	4,45	70	0,290	0,20	
30,0	1 3/16"			7	100	21	300	135,0	5,31	70	0,360	0,25	
32,0	1 1/4"			7	100	21	300	144,0	5,67	70	0,390	0,27	
35,0	1 3/8"			7	100	21	300	158,0	6,22	70	0,440	0,30	
38,0	1 1/2"			6	90	18	270	171,0	6,73	70	0,510	0,35	
40,0	1 9/16"			6	90	18	270	180,0	7,09	70	0,540	0,37	
45,0	1 3/4"			6	90	18	270	203,0	7,99	70	0,670	0,46	
51,0	2"			5	75	15	225	230,0	9,06	70	0,760	0,52	
55,0	2 1/6"			5	75	15	225	247,0	9,72	70	0,810	0,55	
60,0	2 3/8"			5	75	15	225	270,0	10,63	70	0,920	0,62	
63,0	2 1/2"			5	75	15	225	284,0	11,18	70	0,970	0,66	
70,0	2 3/4"			5	75	15	225	315,0	12,40	70	1,160	0,78	
76,0	3"			5	75	15	225	342,0	13,46	70	1,330	0,90	
80,0	3 1/8"			4	60	12	180	360,0	14,17	70	1,450	0,98	
90,0	3 1/2"			4	60	12	180	405,0	15,94	70	1,800	1,21	
102,0	4"			4	60	12	180	459,0	18,07	70	2,190	1,48	
120,0	4 3/4"			3	45	9	135	540,0	21,26	50	2,700	1,82	