

// 266GL



Water S&D - PVC - Standard duty

Construction: green transparent PVC - abrasion and ozone resistant.

Reinforcement: white shock resistant rigid PVC.

Application: water suction and delivery.

Constant operation: -5 °C +60 °C (+23 °F +140 °F)

↔		↔		↻		↻		⌒		⌘	⌚	
mm	in	mm	in	bar	psi	bar	psi	mm	in	%	kg/m	lb/ft
25,0	1"			7	100	21	300	113,0	4,45	70	0,290	0,20
32,0	1 1/4"			6	90	18	270	144,0	5,67	70	0,390	0,27
38,0	1 1/2"			5	75	15	225	171,0	6,73	70	0,510	0,35
45,0	1 3/4"			5	75	15	225	203,0	7,99	70	0,670	0,46
51,0	2"			5	75	15	225	230,0	9,06	70	0,760	0,52
63,0	2 1/2"			5	75	15	225	284,0	11,18	70	0,970	0,66
76,0	3"			5	75	15	225	342,0	13,46	70	1,330	0,90
90,0	3 1/2"			4	60	12	180	405,0	15,94	70	1,800	1,21
102,0	4"			4	60	12	180	459,0	18,07	70	2,190	1,48
127,0	5"			3	45	9	135	597,0	23,50	50	2,900	1,95
152,0	6"			3	45	9	135	714,0	28,11	50	4,000	2,69
203,0	8"			2	30	6	90	954,0	37,56	40	6,200	4,17