

// 266KL



Water S&D - PVC - Standard duty

Construction: yellow transparent PVC - abrasion and ozone resistant.

Reinforcement: white shock resistant rigid PVC.

Application: water suction and delivery.

Constant operation: -5 °C +60 °C (+23 °F +140 °F)

↔		↔		↻		↻		⤴		⌋		⌚	
mm	in	mm	in	bar	psi	bar	psi	mm	in	%	kg/m	lb/ft	
20,0	13/16"			7	100	21	300	90,0	3,54	70	0,230	0,16	
25,0	1"			7	100	21	300	113,0	4,45	70	0,290	0,20	
30,0	1 3/16"			6	90	18	270	135,0	5,31	70	0,360	0,25	
32,0	1 1/4"			6	90	18	270	144,0	5,67	70	0,390	0,27	
35,0	1 3/8"			6	90	18	270	158,0	6,22	70	0,440	0,30	
38,0	1 1/2"			5	75	15	225	171,0	6,73	70	0,510	0,35	
40,0	1 9/16"			5	75	15	225	180,0	7,09	70	0,540	0,37	
45,0	1 3/4"			5	75	15	225	203,0	7,99	70	0,670	0,46	
51,0	2"			5	75	15	225	230,0	9,06	70	0,760	0,52	
60,0	2 3/8"			5	75	15	225	270,0	10,63	70	0,920	0,62	
63,0	2 1/2"			5	75	15	225	284,0	11,18	70	0,970	0,66	
76,0	3"			5	75	15	225	342,0	13,46	70	1,330	0,90	
80,0	3 1/8"			4	60	12	180	360,0	14,17	70	1,450	0,98	
102,0	4"			4	60	12	180	459,0	18,07	70	2,190	1,48	