

## // 268LL



### Pools-spa water circulation

**Construction:** white PVC - abrasion and ozone resistant.

**Reinforcement:** white shock resistant rigid PVC.

**Application:** water circulation systems for pools and SPA. Hose outside diameters made to fit rigid PVC pipe fittings.

**Constant operation:** -5 °C +60 °C (+23 °F +140 °F)

↔		↔		↻		↻		⤴		⌘	⌘	
mm	in	mm	in	bar	psi	bar	psi	mm	in	%	kg/m	lb/ft
28,0	1 1/8"	32,00	1,26	6	90	18	270	168,0	6,61	90	0,250	0,17
32,0	1 1/4"	40,00	1,57	6	90	18	270	192,0	7,56	90	0,540	0,37
42,0	1 5/8"	50,00	1,97	6	90	18	270	252,0	9,92	90	0,780	0,53
55,0	2 1/6"	63,00	2,48	5	75	15	225	330,0	12,99	90	0,840	0,57

## // 195AT



### Compressed air 20 bar (300 psi) - Polyurethane - Pneumatic tools

**Tube:** black polyurethane/PVC - oil mist resistant.

**Reinforcement:** high tensile textile cords.

**Cover:** light blue synthetic elastomer - abrasion and ozone resistant.

**Application:** compressed air.

Specially designed for pneumatic tools and paint spray.

**Constant operation:** -20 °C +60 °C (-4 °F +140 °F)

↔		↔		↻		↻		⤴		⌘	⌘	
mm	in	mm	in	bar	psi	bar	psi	mm	in	%	kg/m	lb/ft
6,0	1/4"	10,00	0,39	20	300	60	900	24,0	0,94		0,065	0,05
8,0	5/16"	12,00	0,47	20	300	60	900	32,0	1,26		0,080	0,06
10,0	3/8"	15,00	0,59	20	300	60	900	40,0	1,57		0,115	0,08
13,0	1/2"	19,00	0,75	20	300	60	900	52,0	2,05		0,185	0,13
16,0	5/8"	23,00	0,91	20	300	60	900	64,0	2,52		0,260	0,18
19,0	3/4"	26,00	1,02	20	300	60	900	76,0	2,99		0,305	0,21
25,0	1"	33,00	1,30	20	300	60	900	100,0	3,94		0,450	0,31

## // 593AK



### Crop spraying 80 bar (1200 psi) - PVC

**Tube:** black PVC.

**Reinforcement:** high tensile textile cords.

**Cover:** yellow ribbed PVC with longitudinal black stripe - abrasion and ozone resistant.

**Application:** crop spraying of fertilizers, pesticides and weed-killers.

**Constant operation:** -5 °C +60 °C (+23 °F +140 °F)

↔		↔		↻		↻		⤴		⌘	⌘	
mm	in	mm	in	bar	psi	bar	psi	mm	in	%	kg/m	lb/ft
8,0	5/16"	15,00	0,59	80	1200	200	2900	64,0	2,52		0,160	0,11
10,0	3/8"	18,00	0,71	80	1200	200	2900	80,0	3,15		0,230	0,16
13,0	1/2"	22,00	0,87	80	1200	200	2900	104,0	4,09		0,320	0,22